

United States Patent Mapes

(10) Patent No.:

US 6,690,620 B1

(45) **Date of Patent:**

Feb. 10, 2004

(54) SONAR TRANSDUCER WITH TUNING PLATE AND TUNING FLUID

(75) Inventor: Theodore J. Mapes, Waitfield, VT (US)

(00)

(73) Assignee: The United States of America as represented by the Secretary of the

Navy, Washington, DC (US)

Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 10/244,922

(22) Filed: Sep. 12, 2002

(51) Int. Cl.⁷ H04R 1/00

(56) References Cited

U.S. PATENT DOCUMENTS

2.906,993 A	*	9/1959	Steinberger	367/152
4,364,117 A	*	12/1982	Snow	367/152
4,694,440 A	*	9/1987	Ogura et al	367/152

* cited by examiner

Primary Examiner—Daniel T. Pihulic

(74) Attorney, Agent, or Firm-James M. Kasischke; Michael F. Oglo; Jean-Paul A. Nasser

(57) ABSTRACT

A method for maximizing the radiated power of a transducer, such as a sonar transducer, includes providing a transducer system comprising a transducer operating at a frequency f and having a radiating face, a tuning fluid having a density ρ_1 and a speed of sound c_1 , a tuning plate having a density ρ_2 and a thickness t, and an external fluid having a density ρ_2 and a speed of sound c_2 ; and tuning the transducer to have a maximum specific acoustic resistance at the radiating face in accordance with the equation:

$$\left[\frac{(2\pi f \rho_p t)^2}{\rho_2 c_2 \rho_1 c_1} + \frac{\rho_1 c_1}{\rho_2 c_2}\right] \rho_1 c_1.$$

The present invention also relates to changing the resonance frequency of a transducer including providing a transducer system with an operating frequency f, the tuning plate spaced from the transducer face by a distance s, and the tuning fluid between the transducer face and the tuning plate and changing the resonance frequency in accordance with the equation

$$\rho_1 c_1 \cot \left(2\pi f \frac{x}{c_1}\right)$$

17 Claims, 1 Drawing Sheet

